

Product Data Sheet



Page: 1

Product Name: **STONE SEAL**

High Performance Clear Multiply Stone Sealer

Stone Seal is a quality aggregate Sealer coating system specifically designed for direct application to various Stone substrates. Including Wet on Wet Concrete.

Stone Seal will provide a water tight durable seal.

It is designed to penetrate and seal with exceptional adhesion. STONE SEAL has resistance to oils , greases and chemicals. STONE SEAL is able to be used internally and externally.

STONE SEAL gives excellent adhesion to a wide variety of substrates including, Concrete substrates, Exposed Aggregate, Grout between ceramic tiles, as sealer on Ceramic substrates e.g. Terracotta Tiles, Slate, Clay and be used to seal Sandstones and Limestone facades and Paving.

STONE SEAL used for pedestrian traffic and vehicle traffic when fully cured.

Physical Data

Product:	Pure Acrylic resin.
Appearance	Viscous liquid, White in colour.
Density	1.Kg/Lt +- 5%
Volume Solids:	~50%
Weight Solids:	~50%
Application Rate	8-10m ² / litre / coat.
Application:	Airless spray, Brush or Roller
Number of coats:	1-3 coats
Touch Dry:	1 hour @ 50um DFT at 25° C
Recoat:	4 hours min
Hard Dry:	8 hours @ 50um DFT at 25°C
Clean-up:	Water
Storage:	Store under cover cool dry conditions up to 2 years.
Classification:	Non Hazardous.
Risk Phrase(s)	Not Applicable

Application Information

Surface Preparation: Surface must be clean free of oil and grease. All loose particles should be removed and repairs carried out to be clean and free of contaminants and treaded.

STONE SEAL applied by hand spray can be diluted up to 5% for better flow through rate.

Application Rate: At 10Lt/m² at a D.F.T. of 50 microns, this would be applied over two or more coats. **Apply thin coats only, to heave a coat will leave milky filming.**

Drying: May vary depending on air temperature, humidity and air flow. Touch dry in 1 to 2 two hours. Dry film cured within 24 hours. Do not apply if temperature is below 10°C or if rain is imminent and relative humidity is >85% above, or heave due.

Equipment Clean up:

Wash all equipment thoroughly with water whilst product is still wet.

Product Data Sheet



Page: 2

Safety Precautions:

Inhalation Seek medical advice if effects persist.
Ingestion Give water to drink. DO NOT induce vomiting. Seek medical advice.
Skin Wash affected areas with copious quantities of water. If swelling, redness, Blistering or irritation occurs seek medical advice.
Eye Contact Remove contact lenses. Immediately irrigate with copious quantity of water for at least 15 minutes. Eyelids to be held open. Seek medical attention.

Protection for First Aiders Wear gloves/safety glasses if contact with concentrate is made.

Typical specification

Surface	Preparation	System	Dry Film Build
Exposed aggregate, Concrete, masonry, brick, cement, cement render and tile, limestone. Pavers,	Thoroughly clean the surface ensuring all traces of loose material and surface contamination (oil, grease etc) are removed. Remove any flaking or peeling paint, acid etch and neutralize.	1. Stone Seal 2. Stone Seal	20 um 20 um

Precautions

Refer to Huecoat Paint Co. Safety Data Sheet (SDS) for health and safety info before use.

Pack Sizes

10 litre, 15litres,20 litre plastic pails, 200 litre drums and 1000 litre Schlitz packs.

Contact information

For further information and technical assistance contact us.

HUECOAT PAINT Co.
U1, 14 Fields Street,
Pinjarra WA. 6208
Tel: 08 9531 1184
Fax: 08 9531 1162
Email:ron@huecoat.com
www.huecoat.com

Disclaimer

This is not a specification, and all the information is given in good faith. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated, the manner of use and whether there is any infringement of patents is the sole responsibility of the user. The manufacturer does not assume any liability in connection with the use of the product relative to coverage, performance or injury. For application in special conditions, consult the manufacturer for detailed recommendations.

- Copyright © 2001-2015 Acebound Nominees Pty Ltd

Huecoat Paint Co.
ABN; 74 247 708 978
Phone; 08 9409 9948
Fax; 08 9409 5194

Email; info@huecoat.com
Web; www.huecoat.com
U1, 49 Prindiville Drive
WANGARA WA. 6065