

RENDER SEAL

RenderPrime

Product Code: HUE015

Product Description

Render Seal is a specially formulated water-based 100% acrylic pigmented primer/sealer that penetrates and seals. It ensures maximum adhesion and consistent surface porosity for the Render paint topcoats. The product is resistant to efflorescence, mould and fungal growth, is quick drying and washes up with water.



Product Features

- ✓ Excellent water resistance
- ✓ Ensures excellent adhesion of topcoats
- ✓ Superb coverage
- ✓ Quick drying
- Easy application and economical clean up.
- Foundation for uniform adhesion & extended durability of subsequent coatings.
- Ensures consistent appearance and finish of total system.

Where to use

Sand cement render, clay and cement brickwork, cement sheet, Precast concrete and masonry walls

Typical Properties

Application tools	Brush, roller or spray
Wash up	Water
Dry time	Touch dry 20 minutes Recoat 2 hours
Coverage	Up to 10m ² /L
Colour	White
Sizes	15L
VOC	48g/L
Volume Solids	32%
Film Build	Wet 60um Dry 20um

Surface Preparation

General Surface Preparation & Previously Painted Surfaces	<ol style="list-style-type: none"> 1. Fill cracks, joins and imperfections . 2. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants. Scrape all loose flaking paint.
Masonry, Brick, Concrete, Render	<ol style="list-style-type: none"> 1. New concrete must be cured for at least 28 days prior to coating. 2. Wash & rinse with clean water.
Concrete and Cement render	<ol style="list-style-type: none"> 1. New concrete and cement render must be cured for at least 28 days prior to painting 2. Dust and wash down the surface.
Precast concrete / Tilt Slab Panels	<ol style="list-style-type: none"> 1. New concrete must be cured for at least 28 days prior to painting. Concrete thicker than 100mm requires additional curing of 2 weeks per extra 25mm thickness. 2. Complete General Surface Preparation 3. Prior to coating ensure any bond breakers / mould release agents are removed.



Application

- Optimum application conditions are between 10°C and 30°C. Do not apply if ambient temperature is below 10°C or greater than 30°C or if the temperature will drop to below 10°C during the drying period.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity, at cooler temperatures or higher humidity drying times will be extended
- Stir thoroughly before and during use with a broad flat stirrer
- Apply with brush, roller or airless spray
- Apply 1 even coat of Renderprime over correctly prepared surface
- Apply coating at recommended coverage rate to ensure performance

Thinning

Thinning is not recommended unless spraying; add up to 100ml clean water per litre of paint to achieve acceptable atomisation. Up to 50ml of water can be added per Litre of paint to ease application under very warm conditions.

Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

Safety Directions

Keep out of reach of children. Avoid contact with skin and eyes and inhalation of vapour. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using.

First Aid Instructions

If swallowed, drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 1126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation develops or persists seek medical advice. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice. If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor.

Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as a sealer/primer for paint and coats. Can be use with any other manufacturer's Water Based products, by follow application instructions, Huecoat cannot be held responsible for application. Further information is available in the form of Safety Data and Product Information Sheets from Huecoat Paint www.huecoat.com . We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Huecoat Paints assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Huecoat Paints. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Huecoat Paint Co

U1, 14 Fields Street, Pinjarra WA 6208
A.B.N 74 247 708 978 Ph.08 9351 1184

www.huecoat.com

Date of Perpetration 12/02/2018

RENDER SEAL



Foundation for
uniform adhesion



Ensures
consistent
appearance and
finish of total
system.



.Easy application
and economical
clean up.